



## Summary

[Request a quote](#)

[Catalog](#)

Low Voltage	16
Gender	Standard
Socket / Receptacle	Socket / Receptacle - Fixed Panel Front Mounted
Locking system	Threaded
Size	2W
Series	W - Underwater

## Technical details

### Electrical Configuration

Contact Termination Low voltage	PCB - Straight
R (max)	6.1 mOhm
Insert configuration value	2W.316 - 16 Low Voltage
Rated current	6 Amps
Contact Type	Print (straight)
Contact Dia.	0.7 mm (0.028in)
Low Voltage	16
Gender	Standard

[https://www.lemo.com/int\\_en/solutions/supreme/w-underwater/evg-2w-316-cln.html](https://www.lemo.com/int_en/solutions/supreme/w-underwater/evg-2w-316-cln.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.



## Form & Material

Shell style / Model id	EV - Fixed socket, nut fixing
Socket / Receptacle	Fixed Panel Front Mounted
Housing material	Brass (chrome plated [SAE AMS 2460]) shell and collet nut, nickel plated [SAE AMS QQ N 290] brass latch sleeve and mid pieces
Locking system	Threaded
Keying	1 key (alpha=0, Plug: male contacts, Receptacle: female contacts)
Weight	25.45 g

## Environment

Technical domain	Specialties and Other
Environmental protection (IP rating)	IP68
Minimal temperature	-20°C / +200°C
Climatical Category	20/200/21
Humidity (max)	<=95% [at 60 deg C /140 F]
Shielding (min)	95 dB (10 MHz)
Shielding (min)	80 dB (1 GHz)
Pressure	30 bars
Salt Spray Corrosion	>1000 hr

## Drawings



## Dimensions

	<b>A</b>	<b>B</b>	<b>e</b>	<b>e1</b>	<b>E</b>	<b>L</b>	<b>N</b>	<b>S1</b>	<b>S2</b>	<b>S3</b>
mm.	22.5	21.8	M16x1.0	M20x1.0	9	30.7	9	14.5	18.5	19
in.	0.89	0.86			0.35	1.21	0.35	0.57	0.73	0.75

[https://www.lemo.com/int\\_en/solutions/supreme/w-underwater/evg-2w-316-cln.html](https://www.lemo.com/int_en/solutions/supreme/w-underwater/evg-2w-316-cln.html)

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.